

SCHEDA TECNICA

Gebosil ACRYL-DECO Scellant acrylique pour décorateurs et plaquistes extra rapide

IT
rev 12/2021
p. 1/2

Product Description

RAPID CEM is an express cement with an acrylic-based formulation, ideal for sealing interior and exterior joints. Quick and easy to apply, it does not stain and requires no preparation. Residues can be cleaned up with water. It has the typical granular appearance of cement, can be troweled and shaped. It is extruded like silicone, with a professional 300 ml cartridge gun.

Applications

Materials: concrete, stone, masonry, tile. Excellent UV resistance.

- For sealing and repairing joints, cracks, crevices and holes.
- For fixing tiles and slates.
- For grouting tiles and edges and small chips.
- For filling cavities and holes in masonry.
- For indoor and outdoor use.

Properties

base	acrylic water dispersion
status	thixotropic
skin formation	5 min (23 °C, 50 % R.H.)
density	1.7 g/cm ³
application temperature	+5 °C to +40 °C
operating temperature	-40 °C to +80 °C

Preparation and use

Surfaces should be dry and clean, free of dust and debris, oil, grease, release agents and other similar substances.

After 5 minutes from extrusion, press firmly with a squeegee to complete application.

After 5-10 minutes, remove excess material with a damp brush or sponge.

To allow for better workability, it is recommended to avoid exposing surfaces to sunlight during application.

It is recommended that the product cure completely before painting.

Rinse hands and tools with water after use.

Restrictions

Not suitable for submerged applications or permanent water contact.

Not suitable for expansion joints.

Joints: width: 8 to 18 mm; depth: 4 to 7 mm.

Formats

art.	color	content
CEM01	white	310 ml

Conservation

In its original packaging in a dry place, away from direct sunlight in a cool place at temperatures between +5°C and +25°C, the product has a shelf life of 12 months.

Safety

MSDSs are available upon request.



G&B Fissaggi S.r.l. Italia

C.so Savona 22, 1029 Villastellone (TO), Italia
tel. +39 011 9619433 - fax +39 011 9619382
www.gebfissaggi.com - info@gebfissaggi.com

G&B Fissaggi UK

G&B Fissaggi Vertretung Deutschland

G&B Fissaggi Ibérica

G&B Fissaggi Benelux

G&B Fissaggi France

SCHEDA TECNICA

Gebosil ACRYL-DECO Scellant acrylique pour décorateurs et plaquistes extra rapide

IT
rev 12/2021
p. 2/2

Guarantee

G&B Fissaggi Srl guarantees the inalterability of the product within the limits of its shelf life. Our responsibility can in no case go beyond what is set forth in our Conditions of Sale.

G&B Fissaggi Srl is not liable under any circumstances for accidental or consequential damages.

Responsability

This information and technical indications correspond to our knowledge and experience without, however, constituting a guarantee in relation to the final results or liability arising from any legal relationship. Indeed, in view of the multiplicity of materials, handling and storage conditions, and production and use conditions, all of the above information and indications must be checked in advance by the user according to the specific circumstances of use.